

Product specification sheet

Product	RØDE Wireless GO II - Dual Wireless Microphone System
SKU	cm-RØDE Wireless GO II-dual
Brand	Rode
Category	Audio & Video
Minimum order quantity	1
Unit	—
Unit price	\$255.00
Available quantity	0

Description

Features Dual channel wireless microphone system for recording two sound sources simultaneously Series IV 2.4GHz digital transmission, 128-bit encryption – crystal-clear audio at up to 200m (line of sight), optimised for extremely stable operation in dense RF environments 3.5mm TRS analog output, USB-C and iOS digital output – universal compatibility with cameras, mobile devices and computers On-board recording – over 40 hours of internal memory Option to record each channel separately or combine them for ultimate flexibility in post-production. Safety channel, flexible gain control (three-stage pad, expandable to 10-stage) In-built rechargeable lithium-ion battery – up to 7 hours battery life Compatible with all RØDE Series IV devices, including the Wireless ME, Wireless PRO, RØDECaster Duo, RØDECaster Pro II and Streamer X RØDE Wireless GO II - Dual Wireless Microphone System Specs Acoustic Principle Pre-polarised pressure transducer Polar Pattern Omnidirectional Frequency Range 50Hz – 20kHz Maximum SPL (Mic) 112dB SPL Maximum Input Level (3.5mm) -20dBV Microphone Preamp Gain 20dB Equivalent Noise Level (A-Weighted) 22dBA Power Requirements In-built rechargeable lithiumion battery charged via USB 5V, 0.3A Operating Time Up to 7 hours Analog Inputs 3.5mm TRS (lavalier microphone input) Analog Outputs 3.5mm TRS Transmission Range 200m (line of sight) Computer Connectivity USB Type-C OS Requirements macOS 10.11 above Windows 10 and above